

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
			Rev No. 04
		Last review Date	05/08/2024
		Page	1 of 7

Section 1.
PRODUCT IDENTIFICATION

Product Name	Valve regulated lead acid (VRLA) battery
Other Names	Electric storage, AGM (Absorbed Glass Mat), Lead Acid Battery-Non-Spillable, Gel Battery
Use	Automotive, Industrial Standby Power and Motive Power.
Supplier Name and Address	Century Yuasa Batteries 37-65 Cobalt St Carole Park QLD 4300
Telephone	(07) 3361 6161
Emergency (24 Hours)	(07) 3361 6707
Relevant identified uses	Starting, lighting, ignition for car, truck, DC storage, forklift operation

Section 2.
HAZARDS IDENTIFICATION

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule **S6** *Classified as S6:- Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)*

Signal Word **DANGER**

GHS Classification Metal Corrosion Category 1, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 3, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Carcinogen Category 1A, Reproductive Toxicity Category 1A, STOT - SE (Resp. Irr.) Category 3*, STOT - RE Category 2, Acute Aquatic Hazard Category 1, Chronic Aquatic Hazard Category 1
**LIMITED EVIDENCE*

GHS Label Elements



Corrosive



Acute toxicity



Health Hazard



Environment

IN THE EVENT OF THE INTERNAL BATTERY COMPONENTS BEING EXPOSED

Hazard Statements	H290 May be corrosive to metals	H350 May cause cancer
	H302 Harmful if swallowed	H360 May damage fertility or the unborn child
	H314 Causes severe skin burns and eye damage	H373 May cause damage to organs through prolonged or repeated exposure
	H318 Causes serious eye damage	H400 Very toxic to aquatic life
	H331 Toxic if inhaled	H410 Very toxic to aquatic life with long lasting effects
	H335 May cause respiratory irritation	

IN THE EVENT OF EXPOSURE TO INTERNAL COMPONENTS

Precautionary Statements	<u>Prevention</u>	<u>Response</u>
	P101 If medical advice is needed, have product container or label at hand.	P301+P316 IF SWALLOWED: get medical help immediately Call a POISON CENTER/ doctor
	P102 Keep out of reach of children	P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P103 Read carefully and follow all instructions.	P302+P352 IF ON SKIN: Wash with plenty of water and soap
	P280 Wear protective gloves /protective clothing/ eye protection/ face protection	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected area with water or shower.
	P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P271 Use only outdoors or with adequate ventilation	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P273 Avoid release to the environment	P308+P317 IF exposed or concerned: Get medical help
	<u>Storage</u>	P333+P317 If skin irritation or rash occurs: Get medical help
	P403+P233 Store in a well-ventilated place. Keep container tightly closed	P342+P316 If experiencing respiratory symptoms: Get medical help immediately Call a POISON CENTER/ doctor
	P405 Store locked up	
	<u>Recycle</u> Refer to section 13	
	<u>Disposal</u>	
	P501 Dispose of contents, container to authorised chemical landfill or if organic, to high temperature incineration	P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage P391 Collect spillage

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY		ETQ Document	SDS-00018
			Rev No.	04
			Last review Date	05/08/2024
			Page	2 of 7

Section 3. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient	Identification	Content % weight
Sulphuric Acid <51% (H ₂ SO ₄)	CAS 7664-93-9	10-15%
Lead (Pb)	CAS 7439-92-1	30-40%
Lead Dioxide (PbO ₂)	CAS 1309-60-0	30-40%
Inert material :- ABS resin or Polypropylene Borosilicate glass microfiber or Fumed Silica	CAS 9003-56-9 CAS 9003-07-0 CAS 65997-17-3 CAS 7631-86-9	5-8%

Section 4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye contact	If this product comes in contact with the eyes: - Immediately hold eyelids apart and flush the eye continuously with running water. - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. - Transport to hospital or doctor without delay. - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin contact	If skin contact occurs: - Immediately flush body and clothes with large amounts of water, using safety shower if available. - Quickly remove all contaminated clothing, including footwear. - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
Inhalation	If fumes of combustion products are inhaled: - Lay patient down. Keep warm and rested. - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. - Transport to hospital, or doctor, without delay.
Ingestion	For advice, contact a Poisons Information Centre or a doctor at once. - Urgent hospital treatment is likely to be needed. - If swallowed do NOT induce vomiting. - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. - Observe the patient carefully. - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. - Transport to hospital or doctor without delay.

MEDICAL ATTENTION AND SPECIAL TREATMENT Indication of any immediate medical attention and special treatment needed


Treat symptomatically.	For acute or short term repeated exposures to strong acids: - Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially. - Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling - Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise. - Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.
Ingestion:	- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended. - DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury. - Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. - Limit fluids to one or two glasses in an adult. - Charcoal has no place in acid management. - Some authors suggest the use of lavage within 1 hour of ingestion.
Skin:	- Skin lesions require copious saline irrigation. - Treat chemical burns as thermal burns with non-adherent gauze and wrapping. - Deep second-degree burns may benefit from topical silver sulphadiazine.
Eye:	- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required. - Cyclopaedic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
			Rev No. 04
		Last review Date	05/08/2024
		Page	3 of 7

- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

Section 5. FIRE FIGHTING MEASURES

Recommended Extinguishing Media



Water spray or fog.



Foam



Dry chemical powder.



Carbon dioxide.



BCF\ Vaporising Liquid
(Where regulations permit).



Extinguishing Media Incompatibilities

- Water may cause electrical hazard If terminals not protected. .
- Use extinguishing media suitable for surrounding area.

Specific Hazards Hazardous Decomposition

- Non-combustible.
- Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.

Fire Incompatibility

- Avoid strong bases.
- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Fire Fighting, Special Protective Equipment & Precautions

- **Do not** approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

- Avoid breathing vapours and contact with skin and eyes.

Environmental Precautions

- Prevent, by any means available, spillage from entering drains or water course.

Methods and materials for containment and cleaning up

- With a clean shovel, transfer spilled material into clean-labelled containers for disposal.
- Wash area down with excess water.
- Do not allow water to enter containers of acid as a violent reaction may occur.
- Prevent from entering drains, sewers, streams or other bodies of water. If contamination of sewers or waterways has occurred, advise the local emergency services

Protective Equipment

- Personal Protective Equipment advice is contained in Section 8 of the SDS.

Emergency Procedures

Minor Spills

- Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
- Check regularly for spills and leaks.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.

Major Spills

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.

Section 7. HANDLING AND STORAGE

Safe Handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Handle gently. Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Avoid smoking, naked lights, heat or ignition sources.
- Avoid mechanical and thermal shock and friction.
- Use in a well ventilated area.
- Avoid contact with incompatible materials.
- When handling DO NOT eat, drink or smoke.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
			Rev No. 04
		Last review Date	05/08/2024
		Page	4 of 7

- Conditions for Safe Storage Includes Incompatible**

 - Avoid contact with moisture.
 - Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - No smoking, naked lights, heat or ignition sources.
- Suitable container for Battery contents**

 - Battery is self-contained but it should be kept in a vertical position to prevent leakage of battery fluid
 - DO NOT use aluminium or galvanised containers**
 - All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods.
 - Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division
- Storage incompatibility contents of battery**

 - Avoid reaction with oxidising agents
 - Avoid strong bases.
 - Avoid storage with reducing agents.
 - Avoid reaction with metals and or water
 - Contact with combustible organic matter may cause a fire.
 - Avoid contact with finely divided metals.
 - Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.
 - Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have a pH of less than 7.0.
 - Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces.

 = May be stored together

 = May be stored together with specific preventions

 = Must not be stored together















X

FLAMMABLES

X

EXPLOSIVES

✓

ACUTE TOXIC

X

OXIDISERS

✓

HARMFUL

✓

IRRITANT

✓

CORROSIVE

Section 8. EXPOSURE CONTROLS , PERSONAL PROTECTION

AUSTRALIAN EXPOSURE STANDARDS (Occupational Exposure Limits)

Ingredient	Material name	TWA	STEL
Sulphuric Acid (H ₂ SO ₄)	Sulphuric acid	1 mg/m3	3 mg/m3
Lead (PbO)	Lead, inorganic dusts & fumes (as Pb)	0.05 mg/m3	Not Available
Lead dioxide (PbO ₂)	Lead dioxide	0.05 mg/m3	Not Available

APPROPRIATE ENGINEERING CONTROLS

- Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:
- Process controls which involve changing the way a job activity or process is done to reduce the risk.
 - Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

PERSONAL PROTECTION



Respirator Type
 Not normally required; however if in contact with internal components:-

- Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	E-AUS P2	-	E-PAPR-AUS / Class 1 P2
up to 50 x ES	-	E-AUS / Class 1 P2	-
up to 100 x ES	-	E-2 P2	E-PAPR-2 P2 ^

^ - Full-face
 E = Sulfur dioxide(SO2),



Eye Protection

- Safety glasses with side shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.



Clothing

- Overalls.



Footwear

- Wear safety footwear or safety gumboots

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
		Rev No.	04
		Last review Date	05/08/2024
		Page	5 of 7



Glove Type

- Wear Elbow length chemical protective gloves, e.g. PVC.



Other Protection

- PVC protective suit may be required if exposure severe.
- Eyewash unit

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

The battery is a manufactured article containing a clear mobile acidic liquid. The electrolyte mixes with water. Rectangular plastic casing with exposed terminals for electrical connections. High weight to volume ratio. The hazard of lead acid batteries include:

- CORROSIVE CONTENTS SHORT CIRCUIT** - accidental discharge. Current flow by external short circuit may heat metals to welding temperatures with firehazard; Internal heat generated may boil battery acid with evolution of large amounts of highly corrosive acid mist/vapour. Boiling may develop internal pressure and cause explosion with scattering of acid contents. Battery circuits must include electrical fusible links. Terminals and external metal parts must be insulated. Do not clean terminals, battery top with conducting liquids.
- SPILL** - damage to casing or overturning may cause corrosive acid contents to spill, causing skin burns on contact. Acid reacts quickly with many metals, generating highly flammable and explosive hydrogen gas; may also weaken metal structures. All lead acid batteries must be vented
- Chemical hazards relate to the contents of the battery. Yellow crystalline; does not mix well with water (1%).
- Soluble in acetone.

Odour	Not Available	Lower explosive limits	4.1% hydrogen gas
Odour threshold	Not Available	Vapour pressure (kPa)	Not Available
pH	<1 (for acid).	Vapour density (Air = 1)	>1
Melting point/ freezing point (°C)	Not Applicable	Relative density (Water = 1)	1.2-1.3 (Sulphuric acid electrolyte)
Initial boiling point and boiling range (°C)	95-95.55 °C	Solubility in water (g,L)	Miscible (acid)
Flash point	Not Applicable	Partition coefficient: n-octanol/water	Not Available
Evaporation rate	<1 BuAC = 1 (for acid)	Auto-ignition temperature	Not Available
Flammability	Not Applicable	Decomposition temperature (°C)	Not Available
Upper explosive limits	74.2%	Viscosity	Not Available

Section 10. STABILITY AND REACTIVITY

Reactivity	See section 7	Chemical stability	- Product is considered stable under normal handling conditions. - Stable under normal storage conditions. - Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7	Conditions to avoid	See section 7
Incompatible materials	See section 7	Hazardous decomposition products	See section 5

Section 11. TOXICOLOGICAL INFORMATION

Inhaled	- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. - Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
Ingestion	- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. - Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.
Skin contact	- Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. - Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	- If applied to the eyes, this material causes severe eye damage. - Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely
Immediate effects	As above
Chronic effects	- Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. - Substance accumulation, in the human body, is likely and may cause some concern following repeated or long-term occupational exposure.

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
		Rev No.	04
		Last review Date	05/08/2024
		Page	6 of 7

- Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

Sulphuric Acid:

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyper reactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. Occupational exposures to strong inorganic acid mists of sulphuric acid:

Lead:

WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.

Acute Toxicity	Skin Irritation/Corrosion	Serious Eye Damage/Irritation	Respiratory or Skin sensitisation	Mutagenicity	Carcinogenicity	Reproductivity	STOT - Single Exposure	STOT - Repeated Exposure	Aspiration Hazard
✓	✓	✓	ⓘ	ⓘ	✓	✓	✓	✓	ⓘ

✓ = Data required to make classification available ✗ = Data available but does not fill the criteria for classification

ⓘ = Data Not Available to make classification

Section 12. ECOLOGICAL INFORMATION

- | | |
|-----------------------------------|---|
| Ecotoxicity | <ul style="list-style-type: none"> Prevent, by any means available, spillage from entering drains or water courses. DO NOT discharge into sewer or waterways. |
| Degradability | <ul style="list-style-type: none"> No Data available for all ingredients |
| Bio-accumulative Potential | <ul style="list-style-type: none"> No Data available for all ingredients |
| Mobility in Soil | <ul style="list-style-type: none"> No Data available for all ingredients |
| Other Adverse Effects | <ul style="list-style-type: none"> No Data available for all ingredients |

Section 13. DISPOSAL CONSIDERATIONS

- | | |
|---|---|
| Safe Handling & Disposal | <ul style="list-style-type: none"> Dispose in accordance with federal, state or local regulations. |
| Disposal of Contaminated Packaging | <ul style="list-style-type: none"> Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurring in water; Neutralisation followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material) Decontaminate empty containers. |
| Environmental Regulations | <ul style="list-style-type: none"> Refer to section 15 |

Section 14. TRANSPORT INFORMATION

REGULATED FOR TRANSPORT OF DANGEROUS GOODS ADG

- | | |
|-------------------------------|---|
| UN Number | 2800 |
| Proper Shipping Name | BATTERIES, WET, NON-SPILLABLE, electric storage |
| Transport Hazard Class | Class: 8 Sub risk: Not Applicable |
| Packing group | Not Applicable |
| Environmental Hazards | No relevant data |
| Special Precautions | Special provisions 238
Limited quantity 1 L |
| Additional Information | Marine Pollutant: = Yes |
| Hazchem Code | 2R |
| Other Information | The Australian Dangerous Goods Code (7th Edition) Special Provision 238 allows Century Yuasa Batteries Pty. Ltd. to transport non-spillable batteries as sold by the company by road and rail as non-dangerous goods. In addition, these batteries are certified as complying with UN2800 Special Provision A67 of the International Air Transport Association (IATA) Dangerous Goods Regulations. Refer to Century Yuasa Batteries office for further information. |



Section 15. REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS, LEGISLATION

	AU SAFETY DATA SHEET VALVE REGULATED, AGM, GEL, NON-SPILLABLE BATTERY	ETQ Document	SDS-00018
		Rev No.	04
		Last review Date	05/08/2024
		Page	7 of 7

Sulphuric Acid CAS 7664-93-9 Is found on the following regulatory Lists "Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Hazardous Substances Information System - Consolidated Lists"

Lead CAS 7439-92-1 Is found on the following regulatory Lists "Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"

Lead dioxide (PbO₂) CAS 1309-60-0 Is found on the following regulatory Lists "Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"

Section 16. OTHER RELEVANT INFORMATION

Revision Information	Revision N°	Date	Description
	1	29/10/15	Initial SDS creation
	2	01/02/2017	Adjusted to lead dioxide; included Inert material
	3	03/04/18	Sect 14 Altered provisions to 238
	4	11/09/19	Title changed adjusted Exposure Limits
	ETQ 01	01/09/23	Updated for ETQ
	02	23/11/23	Minor Adjustment Revision
	03	24/11/23	Adjusted for poor PDF
	04	05/08/24	Reviewed updated to GHS 10e

Abbreviations

AICS	Australia Inventory of Chemical Substances
APVMA	Australian Pesticides and Veterinary Medicines Authority
AQIS	Australian Quarantine and Inspection Service
CAS #	Chemical Abstract Service Number – <i>used to uniquely identify chemical compounds</i>
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration- <i>toxicity of the surrounding medium that will kill half of the sample population of a specific test-animal in a specified period through exposure via inhalation (respiration)</i>
SDS	Safety Data Sheet- (SDS), <i>previously called a Material Safety Data Sheet (SDS)</i> ,